

DATA SHEET

COD. **2708W**

DOOR-ENTRY PHONE W/ 2 BTNS FOR SIMPLEBUS AUDIO. MINI SER.

MINI series door-entry phone for Simplebus system with electronic call, key button and additional button for extra services (switchboard call, actuator, generic uses). Call volume and privacy adjustment by means of 3-position selector. Privacy activation is indicated by a red light. Allows floor door call management. Complete with 8-position dip-switch for selection of the desired user code. Dimensions: 105x191x28 mm



General specifications

System:	SimplebusTop (S1)
Audio system:	Yes
Wall-mounted:	Yes
Desk base-mounted:	Yes
Hands-free function:	-
Induction loop function:	-
Product color:	Bianco
Total buttons:	2
LED signaling:	No

Functions

Actuator control function:	Yes
Switchboard call function:	Yes
Panic call:	-
Intercom function:	-
Selective intercom call:	-
Privacy function:	Yes
Doctor:	-
Floor door call function:	Yes
Electronic bell:	Yes
Customisable ringtone:	-
Key button function:	Yes

Settings

Loudspeaker volume control:	Yes
Ringtone volume control:	Yes

DATA SHEET

General info

Product height (mm):	190
Product width (mm):	103
Product depth (mm):	30

Technical specifications

Supply voltage:	20 ÷ 28 Vdc
Power consumption stand-by (mA):	0,710 ÷ 0, 715 mA
In called absorption (mA):	20 ÷ 23 mA
In communication absorption (mA):	20 ÷ 22 mA
Microphone:	Ø 9,6 x 6,9 mm
Speaker:	Ø 0,50 mm ; Max Input Power 0,5W
IP Rating:	30
Operating temperature (°C):	-5÷40
Product weight (g):	0,257 Kg
Clamps:	L,L,CFP,CFP