

**3012/2/RI/B****ROMA SERIES AUDIO ENT. PANEL FOR IKALL UNIT, 12
BUTT.-BRONZE**

Door-entry phone entrance panel with bronze finish front plate in 3 mm thick watchmaking brass plate with PVD treatment. Complete with flush-mounted box and anti-intrusion screws. All entrance panels are fitted with bulb sockets (without bulb) for festoon bulbs with a diameter of 6.3 x 39 mm. The keypad should be finished with an audio speaker unit depending on the wiring system used. 12 buttons, 2 rows. Plate dimensions 180x362x3 mm. Box dimensions 160x305x55 mm. 2 lamp sockets



3012/2/RI/B

**ROMA SERIES AUDIO ENT. PANEL FOR IKALL UNIT, 12
BUTT.-BRONZE**

**3012/2/RI/B****ROMA SERIES AUDIO ENT. PANEL FOR IKALL UNIT, 12
BUTT.-BRONZE****1622VC 2 WIRES IKALL AUDIO UNIT FOR REMOTE CAMERA**

Module which allows modulation and transmission of the colour video signal on the riser. On input it has the composite video signal of a colour camera. Complete with microprocessor and DIP SWITCH with 8 positions for programming calls to users. 33Vdc power supply via special power supply unit Art. 1595. On-board electronic lock-release function (3A), plus C, NC, NO contacts for 10A relay. For use in modules Art. 33400, 33401 and 33402. Dimensions: 102x55x38 mm. Compatible with all Simplebus 2 functions and products. It allows call addressing for up to 120000 users. Timed lock-release inputs and door open indication.

**1172 VANDALCOM 12/24V BULBS**

24V/3W festoon bulb for illuminating name labels.