DATA SHEET

COD. 3072B

SIMPLEBUS DIGITAL DIRECTORY MODULE, VANDALCOM SERIES

Made using a double 2.5 mm stainless steel plate, complete with 4 backlit stainless steel buttons and 32-character alphanumeric display. Stores up to 1000 usernames. 2 search buttons are used to scroll though the names. Once the desired name is displayed, simply press the call button. User programming is easy, thanks to programmer art. 1230 or PC software art. 1231/6D. Dimensions: 106x106x56 mm. From IR10 it is compatible with all SBTOP products and functions. It can be used for the call addressing of up to 120000 users.

	Backlighting colour:	LED GREEN	
oftwa	are/firmware specifications		
	No. user codes:	1500	
	No. of storable users:	1500	
ardw	are specifications		
	Vandal Resistant IK:	Yes	
	Customisable housing:	No	
	DDE function:	No	
	Total buttons:	4	
	Sensitive Touch technology:	No	
	Key button function:	No	
enera		100	
	Product height (mm): Product width (mm):	106	
	Product depth (mm):	56	
	Product colour:	GREY	
	Operating temperature (°C):	-25/55	
	Intrastat code:	85176920	
		03170320	
ompa	atibility		

Passion. Technology. Design.

0

The technical specifications are subject to variations without warning

DATA SHEET

Simple	ebus Color system:	Yes	
Simple	ebus 2 system:	Yes	
Mounting/Inst			
Flush-	mounted:	Yes	
Wall-m	nounted:	Yes	
Surfac	e-mounted:	Yes	
Audio/video s	pecifications		
	y resolution (H x V):	16x2 characters	
Audio	system:	Yes	
Audio/	video system:	Yes	
Туре с	of display:	Alphanumeric	
Connectivity			
•	of connections/ports:	RS232, RS485, INFRARED	
Infrare		Yes	
RS232	2 ports:	1	
RS485	5 ports:	1	
Electrical spe	cifications		
-	uum current absorption (mA):	100	
Packaging			
Single	pack height (mm):	88	
Single	pack width (mm):	113	
Single	pack weight (Kg):	0,747	
Cinada	pack depth (mm):	111	
Single	puok dopti (min).		

