

DATA SHEET

COD. **3451AS**

STAINLESS STEEL SBC DIG. 316 SENSE AUDIO ENT.PAN.

Flush-mounted entrance panel (fitted level with the wall) and 3 mm thick stainless steel plate. Certified as IK08. Complete with 128x64 dot LCD graphic display and 15 buttons integrated into the plate, with no mechanical movement. Also functions as an electronic key code. Two search buttons are used to scroll through the names; alternatively, the first letter of the required name can be entered. Once the desired username is displayed, simply press the call button. The call can also be made by directly entering the user code. It can also be used to customise an initial welcome message and can operate with a dual user interface language. Fitted with rfid reader for local door lock control and an additional relay for various uses. It can be used in conjunction with Simplekey electronic keys for automatic updating of names in the directory. It saves up to 4000 user names, 4000 lock-release passwords and 4000 rfid keys. Users and settings are simple to program using PC software art. 1249B (included, with USB connection cable) via a USB or RS485 port, locally on the digital module itself or, thanks to the integrated web server, remotely via connection to the ethernet port. It is compatible with all SBTOP products and functions. Complete with audio unit Art. 1622 for audio/door lock management, and flush-mounted box with concealed fixing screws. To be powered at 33 Vdc using art. 1595. Dimensions 342x182x3 mm



General specifications

Compatible with audio group:	Yes
Flush-mounted:	Yes
Wall-mounted:	Yes
Loudspeaker volume control:	Yes
Operating temperature (°C):	-25 ÷ 55
Vandal Resistant IK:	IK08

Functions

Key button function:	Yes
----------------------	-----

Hardware specifications

Visual signalling:	Yes
Acoustic signalling:	Yes
Sensitive Touch technology:	Yes

General info

Product height (mm):	342
Product width (mm):	182
Product depth (mm):	3

Compatibility

Simplebus Top system:	Yes
Video door entry family:	Yes