

# AYC-E65B(G/W/B)

## Ultra-Slim Piezo Mullion Backlit PROX & PIN Reader – Convertible



**UNIQUE ULTRA-SLIM PROFILE, SMOOTH METALLIC SURFACE AND HIGH SENSITIVE PIEZOELECTRIC KEYS, NOW COMBINED WITH SHINY ILLUMINATED DIGITS AND A PROXIMITY CARD READER MAKES THIS UNIT HIGHLY ATTRACTIVE FOR ALL-WEATHER PIN & PROX ACCESS APPLICATIONS. FULLY POTTED IN A METAL HOUSING, THE AYC-E65B OFFERS HIGHLY ATTRACTIVE YET DURABLE SOLUTION FOR ANY NEED. PART OF THE CONVERTIBLE LINE OF READERS/CONTROLLERS, THIS UNIT CAN BE OPERATED AS A KEYPAD READER WITH ANY STANDARD CONTROLLER, AND CONVERTS INTO A SECURE 500-USER CONTROLLER WHEN CONNECTED TO THE PS-x25T INTELLIGENT POWER SUPPLY/RELAY UNIT.**

### GENERAL DESCRIPTION

For greater peace of mind, this sturdy access control unit provides a rugged keypad with advanced access control features, in a unique aesthetic and strong housing.

The AYC-E65B offers programmable PIN & Proximity transmission formats, LED control and tamper detection, providing extra security and flexibility. Come rain or shine, this unit can handle the challenge, with its rugged metallic housing and waterproof enclosure for maximum durability.

The high sensitivity, illuminated piezoelectric keypad, with its auto-dimming options is clearly visible day or night, allowing easy and smooth operation making these units ideal for residential and commercial applications.

### MAIN FEATURES

- Supports 4- to 8-Digit PIN credentials and 125 KHz EM type RFID cards and tags
- Smooth, attractive design, with all-weather indoor and outdoor operation
- Large, high-visibility unique illuminated piezoelectric keypad
- Optical back tamper detection output

- 2 tri-colored LEDs and an integral sounder for programming and operation
- User-friendly menu system based on keypad, LED, and sounder indicators
- Automatically recognizes a connection to PS-x25T intelligent power supplies and converts into a 500-user standalone controller with secure relays
- Available in three models: AYC-E65BG with gray antenna, AYC-E65BW with white antenna, and AYC-E65BB in black

### PROFESSIONAL GRADE FEATURES

- 8 selectable PIN transmission modes including options for Key stream, Binary, Parity, and 2x6 Matrix
- Supports Wiegand or Clock & Data transmission formats
- 3 security levels (controller mode): Bypass (free entry), Normal (card or PIN required) or Secure (card + PIN)
- Comes with a mounting and drilling label
- 60 cm (23.6 in.) shielded interface cable

# SPECIFICATIONS

## ELECTRICAL SPECIFICATIONS

|                           |  |
|---------------------------|--|
| ■ Operating Voltage Range | Reader mode: 5 to 16 VDC from a standard controller<br>Controller mode: PS-x25T series intelligent power supplies  |
| ■ Input Current           | Standby: 92 mA @ 12 VDC, Maximum: 105 mA @ 16 VDC  |
| ■ Proximity Card Reader   | Maximum read range*: 40 mm (1.6 in.)<br>Modulation: ASK at 125 kHz<br>Compatible cards: All 26-Bit EM Cards<br>* Measured using Rosslare Prox Card AT-R14 or equivalent. Range also depends on electrical environment and proximity to metal |
| ■ Tamper                  | Open collector, active low, 30 mA max sink current   |

## OPERATIONAL SPECIFICATIONS

|                |  |
|----------------|--|
| ■ Keypad       | 2x6 blue illuminated keys (Always On, Always Off and Auto Dimming options) for local programming and 4- to 8-digit PIN codes entry                                       |
| ■ Design       | Epoxy potted, fully sealed in a rugged thin metal enclosure, highly strong construction and high sensitive piezoelectric keys. Suitable for extremely harsh environments |
| ■ Audio/Visual | Two tri-colored LED indicators, built-in buzzer  |

## READER MODE

|                     |  |
|---------------------|--|
| ■ LED Control       | Dry contact, N.O.  |
| ■ Facility Code     | Programmable   |
| ■ Card Read Formats | Selectable Wiegand 26-Bit or Clock & Data                |
| ■ PIN Code Formats  | 8 selectable formats, from 1 to 8 digit length PIN Codes |

## CONTROLLER MODE

|   |  |
|---|--|
| Available with PS-x25T series intelligent power supplies only |  |
| ■ Capacity  | 500 users, single/dual PIN code each                                       |
| ■ User Levels   | Normal, Secure and Master  |
| ■ Security Modes  | Normal, Bypass and Secure  |
| ■ Outputs   | Lock Strike output, Auxiliary output (PS-x25T series)                      |
| ■ Inputs  | REX (Request to Exit)<br>Auxiliary/Door Monitor with 10 programmable modes |

## ENVIRONMENTAL SPECIFICATIONS

|                         |  |
|-------------------------|--|
| ■ Operating Environment | All weather, indoor and outdoor use, meets IP 68 |
| ■ Operating Temperature | -30°C to 65°C (-22°F to 150°F)                   |
| ■ Operating Humidity    | 0 to 95%   |

## PHYSICAL SPECIFICATIONS

|              |  |
|--------------|--|
| ■ Dimensions | 155 x 44 x 9 mm (6.1 x 1.73 x 0.354 in.) |
| ■ Weight     | 143 g (0.315 lbs)                        |

## SYSTEM COMPONENTS

|  |  |
|--|--|
|  | AYC-E65B (Reader mode) is compatible with standard access controllers. With Rosslare's PS-x25T intelligent power supplies series, it automatically converts into a 500-user secure controller. |
|--|--|

## PRODUCT WARRANTY

|  |                                 |
|--|---------------------------------|
|  | 5-year Limited Product Warranty |
|--|---------------------------------|

## ABOUT ROSSLARE SECURITY

Rosslare Security Products, a division of Rosslare Enterprises Ltd., has been manufacturing high-quality security products since 1980. The company's three main lines – Access Control, Intrusion Detection and Guard Patrol – together with a growing product range have transformed Rosslare Security into a major worldwide force in security. Rosslare holds itself to the highest standards of customer service and manufacturing (ISO 9001:2008, ISO 14001:2004, ISO 13485:2003). The company complies with the EU Directive 2002/95/EC on Restriction of Hazardous Substances (RoHS). Visit our website: [www.rosslaresecurity.com](http://www.rosslaresecurity.com)

