



2 Mega-Pixel CMOS Day&Night IP Camera

CAM613M(W, PoE)



- 2 Mega-Pixel CMOS sensor
- ► H.264/ MJPEG/ MPEG4 Triple mode & streaming
- ▶ Support SD card for event recording
- Support DC IRIS
- 2-way audio / 1 Analog video output
- ▶ Digital I/O: 1 in/ 1 Relay out
- ▶ 3GPP for monitoring via 3G mobile phone
- ▶ Embedded Wireless (CAM613M-W)
- ► Embedded PoE (CAM613M-PoE)

Specification

Hardware

CPU/ RAM/ Flash ARM 9, 32 bit RISC/ 256MB/ 16MB

Image Sensor 1/3" CMOS, 2 Mega-Pixels

Lens Fixed Lens 3.7 mm, Mega Pixel @ F1.8

Illumination 0.5 lux

Day/ Night Optional Mechanism IR Cut Filter (ICR)

Lens Changeable Yes, CS Mount

Support DC IRIS Yes

Video Out 1 Analog video out (BNC connector)

Audio In Built-in microphone

Audio Out 1 Line out (RCA connector)

Digital I/O 1 In / 1 Relay out

Power Supply CAM613M/ CAM613M-W: DC 12V, 1A

CAM613M-PoE:

Use PoE: PoE Injector (IEEE 802.3af) Or, use Power Adapter: DC 12V, 1A

Dimensions W58 x H65 x D131.5 mm

Network

Ethernet 10/100 Base-T

Wireless 802.11b/g (CAM613W)

WEP,WPA-PSK,WPA2-PSK

Network Protocol HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, UDP

FTP, SMTP, PPPoE, DHCP, DDNS, UPnP

Client Requirements

OS Windows XP / Vista / Win 7

Browser IE7,IE8, FireFox, Safari, Chrome, Opera Suggested Intel Core 2 Duo 1.66GHz, RAM: 1GB

Graphic card: 128MB onboard RAM

System

Video Resolution 1600x1200,1280x1024,1280x960,1280x720,

800x592,640x480, 320x240, 176x144

Compression Format H.264 / MJPEG / MPEG-4 (3GPP only)

Frame Rate Up to 15 FPS@1600x1200

Up to 30 FPS@1280x720

Video Bitrate Adjust CBR, VBR

Triple Streaming Yes (2 for live view, 1 for 3GPP)

3GPP Yes, Live view with 3G mobile phone

Video Adjust Night Mode, Brightness, Contrast, BLC,

Sharpness

Motion Detection Yes, 3 different areas
Pre/ Post Alarm Yes, configurable
Security Password protection

Connection Up to 10 clients simultaneously

Firmware Upgrade HTTP mode, remotely

Audio Yes, 2-way

Event System

Event Trigger Motion Detection, Sensor In

Trigger Actions Send Email, Send to FTP, Save to SD Card,

Relay Out

SD Card Management

Recording Trigger Motion Detection, Sensor In, IP Check,

Network Disconnect

Video Format Video (AVI), Snapshot (JPEG)
Schedule Snapshot during schedule

Video Playback / Delete Yes

Package List

Camera, Power Adapter (not included with PoE model), Ethernet Cable, Antenna(CAM613M-W), Tool, CD-ROM, Quick Guide

http://www.a-soni.com

E-mail: marketing@a-soni.com

* Specifications are subject to change without notice