Network Surveillance Solutions

/soni

2 Mega-Pixel CMOS Day&Night Vandal Dome

CAM619M(PoE)

- 2 Mega-Pixel CMOS Sensor
- ▶ H.264/MPEG4/MJPEG Triple mode & streaming
- Support SD card for event recording
- ▶ IP-66 waterproof standard
- ▶ 3GPP for monitoring via 3G mobile phone
- 1 Analog video output
- 2-way audio
- Embedded PoE (CAM619M-PoE)
- Free 36CH recording software

Specification

Hardware

| Taluwale | |
|------------------|---|
| CPU | ARM 9, 32 bit RISC |
| RAM | 256MB |
| Flash | 16MB |
| Image Sensor | 1/3" CMOS, 2.0 Mega pixels |
| Lens | Vari-focal 2.7 ~ 9 mm |
| Day / Night | Embedded IR Cut Filter (ICR) |
| Illumination | 0.5 lux |
| Video Out | 1 Analog video out (BNC connector) |
| Audio In/ Out | 1 Mic in / 1 Line out |
| Digital I/O | 1 In / 1 Relay out |
| Water Proof | IP-66 standard |
| Power Supply | CAM619M: DC 12V, 1A |
| | CAM619M-PoE: |
| | Use PoE: PoE Injector (IEEE 802.3af) |
| | Or, use Power Adaptor: DC 12V, 1A |
| Dimensions | Ф138 x H105 mm |
| Network | |
| Ethernet | 10/ 100 Base-T |
| Network Protocol | HTTP, TCP/IP, RTP/RTSP, 3GPP, NTP, |
| | SMTP, FTP, PPPoE, DHCP, DDNS, UPnP |
| Event System | |
| Event Trigger | Motion Detection, Sensor In |
| Trigger Actions | Send Email, Send to FTP, Save to SD Card, |
| | Relay Out |
| Client Requirer | nents |
| OS | Windows XP / Vista / Win 7 |
| Browser | IE7,IE8, FireFox, Safari, Chrome, Opera |
| Suggested | Intel Core 2 Duo : 1.66GHz, RAM: 1024MB, |
| | Graphic card: 128MB onboard RAM |

System

| Video Resolution | 1600x1200, 1280x1024, 1280x960, |
|----------------------|---------------------------------------|
| | 1280x720, 800x592, 640x480, |
| | 320x240,160x120 |
| Compression Format | H.264 / MJPEG / MPEG-4 (3GPP only) |
| Frame Rate | Up to 15 FPS@1600x1200 |
| | Up to 30 FPS@1280x720 |
| Video Bitrate Adjust | CBR, VBR |
| Triple Streaming | Yes (2 for live view, 1 for 3GPP) |
| 3GPP | Yes, Live view with 3G mobile phone |
| Image Snapshot | Yes |
| Video Adjust | Brightness, Contrast, Sharpness, BLC, |
| | Night Mode |
| Motion Detection | Yes, 3 different areas |
| Pre/ Post Alarm | Yes, configurable |
| Security | Password protection |
| Connection | Up to 10 clients simultaneously |
| Audio | Yes, 2-way(Duplex Support) |
| Firmware Upgrade | HTTP mode, remotely |
| | |

SD Card Management

| Recording Trigger | Motion Detection, Sensor In, IP Check, |
|-------------------------|--|
| | Network Disconnect |
| Video Format | Video (AVI), Snapshot (JPEG) |
| Schedule | Snapshot during schedule |
| Video Playback / Delete | Yes |

Package List

Camera, Power Adapter (not included with PoE model), Ethernet Cable, Screws&Tool, CD-ROM, Quick Installation Guide

http://www.a-soni.com

E-mail: marketing@a-soni.com

