GCH-K0305B

2 Megapixel Full HD CMOS Box HD-SDI Camera ICR WDR



- Full HD, 1920 x 1080p, 25/30 fps over coax
- Digital Noise Reduction
- WDR function, Colour/B&W function with removable IR cut filter
- Back light compensation for various light conditions
- Power Input AC24V/DC12V

SUMMARY

Based on the Television Standard for FullHD Television, HD-SDI products feature up 2 Megapixel (1920x1080) pictures in real-time (30fps) transmitted over coax cabling.

Get the advantages of IP technology without their drawbacks. Get 16:9 megapixel pictures without network configuration, bandwidth problems and network security risks. Use existing coax cables and only exchange the cameras and recorders. Get a "real" live picture and see the things that happen in the now, not a few seconds ago. Connect a monitor directly to a camera using only a HD-SDI-to-HDMI converter.

HD-SDI products are easy to handle, easy to install and produce amazing high quality pictures.

SPECIFICATIONS

| Image Sensor | 1/2.8" Progressive Scan CMOS, 3 Megapixels |
|-------------------------------|---|
| Pixels - Total | 2144(H) x 1588(V), 3.40M pixels |
| Pixels - Effective | 2080(H) x 1553(V), 3.23M pixels |
| Scanning System | Progressive |
| Image Size | 1920x1080, 1280x720 |
| Frame Rate | 30/60, 25/50 fps at 1080p; 30/60, 25/50 fps at 720p |
| Sensitivity Colour | 1.44 lux @ F1.2 (50IRE) |
| Sensitivity B&W | 0.72 Lux@F1.2 (IRE50) |
| Video Outputs | 1 Ch HD-SDI BNC or 1 Ch Composite BNC |
| Lens Mount | C/CS mount |
| Lens Drive Type | DC auto iris, manual iris |
| High Speed Shutter | 1/25 ~ 1/10,000 sec |
| Shutter Mode | Auto / Fix / Iris / Manual |
| Col/B&W | On/Off/Auto |
| Protocol | Pelco D, Pelco P, |
| Serial Interface(s) | RS-485 |
| OSD | Yes |
| Number of Privacy Zones | 16 |
| BLC | On/Off |
| Digital Noise Reduction (DNR) | On/Off |
| White Balance | Auto, Manual, Indoor, Outdoor, ATW |
| Operating Temperature | 0°C ~ +50°C |
| Humidity | 10 ~ 90% no condensation |
| Supply Voltage | 12 VDC/24 VAC |
| Power Consumption | 5 W |
| Weight | 0.33 kg |
| Dimensions w*h*d | 82 x 52 x 125 mm |
| | |

ACCESSORIES



GTH-K0011E 1Ch HD-SDI Repeater & 2 Ch Distributor



GTH-K0010M 1Ch HD-SDI to HDMI converter



GRH-K1004A 4 Channel H.264 HD-SDI Recorder with DVD-RW Drive