



**IX0101CO**

**SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM**



Front plate for Switch entrance panel in 2.5 mm thick brushed AISI 316 stainless steel, designed to house SimpleKey or third-party access control readers. Adapter art. 1250U (supplied) offers the option of using the audio or audio/video module (not supplied), depending on the type of wiring applied (Simplebus digital 2-wire or ViP). Complete with 1 pre-fitted, pre-wired button. White LED nameplate backlighting. IK08 protection rating. To be finished with flush-mounted box or surface-mounted casing. Panel dimensions: (L x H): 150x262.7 mm. Hole dimensions: 40x40 mm.

**AWARDS**

DESIGN  
MILANO



**IX0101CO**

**SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM**

**GENERAL DATA**

Type	Monoblock
Product height (mm)	262.7
Product width (mm)	150
Product depth (mm)	2.5
Product colour	Steel
Material	Stainless steel AISI 316
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Compatible audio and audio/video units	Art.1682, Art.1682HVC, Art.4682HD, Art.1621, Art.1622, Art.1622VC, Art.4680C, Art.4681
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210	Yes
Simplebus 2 audio/video kit with power supply art. 1209	Yes
Audio Simplebus 2 with power supply art. 1210	Yes
Audio Simplebus 1	Yes
ViP	Yes

**HARDWARE FEATURES**

Call type	Push-buttons
Type of buttons	Mechanical
Number of push-buttons (n°)	1
Backlight colour	White

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection degree	IP54
----------------------	------



**IX0101CO**

**SWITCH FRONT PLATE, 1 BUTTONS+HOLE 40X40MM**

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IK vandal-proof protection degree	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max - %) (%)	25 ÷ 75
Environmental class	III