

Color IR Dome Cameras

JCC-VIR966D

1/3" Color IR Dome Camera

JCC-VIR966HQD

1/3" High Res.Color HQ1 IR Dome Camera



Features

- ✦ JCC-VIR966D
 - 1/3" interline transfer CCD
 - NTSC:537x505/PAL:537x597
 - 420 TV Lines / 0 Lux with IR
- ✦ JCC-VIR966HQD
 - SONY HQ1 DSP
 - NTSC:811x508/PAL:795x596
 - 540 TV Lines / 0 Lux with IR
- ✦ Automatic Gain Control (AGC)
- ✦ Full Auto BLC
- ✦ 0.45 Gamma Characteristic
- ✦ 28 x IR-LED (850 nm) Built-in
- ✦ 15 Meters Illuminating Range
- ✦ DC 12V
- ✦ 3.5 ~ 8.0 mm Varifocal Lens
- ✦ Focus & Zoom Available Adjustment Outside Camera

Specification

Model	JCC-VIR966D	JCC-VIR966HQD
Pick Up Element	1/3" SONY Super HAD CCD	1/3" SONY Super HAD CCD
DSP	SONY DSP	SONY 10-bit HQ1 DSP
Picture Element	NTSC:537(H)x505(V) ; PAL:537(H)x597(V)	NTSC:811(H)x508(V) ; PAL:795(H)x596(V)
Horizontal Frequency	NTSC: 15.734 KHz ; PAL: 15.625 KHz	
Vertical Frequency	NTSC: 59.94 Hz ; PAL: 50 Hz	
Synchronization	Internal	
Scanning System	2 : 1 Interlace	
Resolution	Horizontal 420 TV Lines	Horizontal 540 TV Lines
Sensitivity	0.5 lux @F2.0 (Day) ; 0 Lux (IR on)	0.5 Lux @F2.0 (Day) ; 0 Lux (IR on)
Scanning System	2 : 1 Interlace	
S/N Ratio	More than 48dB (AGC OFF)	
Electronic Shutter	Auto;(1/60-100,000 sec)NTSC; (1/50-100,000 sec)PAL	
Lens	3.5 ~ 8.0 mm Varifocal Lens	
Video Output	1.0 Vp-p Composite Video Output; 75 Ohms	
Water Resistance	IP66	
IR Distance	More than 15M (28 pcs IR LED)	
IR trigger	3.1Lux/3.7Lux IR ON/OFF	
Power Supply	DC 12V	
Power Consumption	Max. 5.9W	
Current	490mA	
Dimension	119mm(Dia.) x 82.5mm(H)	
Operation Temperature	- 10° ~ +50 °C / RH 85% or Less	

Dimension

