Speed Dome Installation Accessories



Dyna**Hawk**™ Installation Accessories

The DynaHawk™ speed dome camera series offers a wide range of accessories to facilitate all surveillance installations, including various indoor and outdoor mountings, special optical covers to match and complement the surroundings, and power supplies for different voltage requirements.

The DynaHawk™ speed dome camera series is designed with various mounting options. Users can select the most suitable accessories to complete the installation depending on the camera mounting requirements. With various types and sizes of accessories, users can mount the camera in virtually any environment.

Indoor Dome Accessories

Transparent / Vandal Proof Cover

4.3" Optical Cover Diameter: 109 mm (4.3 inches) Compatible with: DH500

5.4" Optical Cover Diameter: 137 mm (5.4 inches) Compatible with: DH701



5.4" Smoke Cover Diameter: 137 mm (5.4 inches) Compatible with: DH701

Smoke Cover



Power Adapter

D77H07-A1015

Input: 100~115VAC / Output: 24VAC 36VA

D77H07-A2015

Input: 220~230VAC / Output: 24VAC 36VA




Connector Box

The D77H07-C00 connector box provides easy wiring and well organized connection between alarms, cameras and other devices, for easy installation.

Dimension: 92×42 mm (3.7×1.7 inches) Weight: 0.13 kg (0.3 lbs)



System Configuration



Outdoor Dome Accessories

Transparent / Vandal Proof Cover

5.4" Optical Cover Diameter: mm (5.4 inches) Compatible with: DH600

5.8" Optical Cover Diameter: 147 mm (5.8 inches) Compatible with: DH801+





Smoke Cover

5.4" Smoke Cover Diameter: 137 mm (5.4 inches) Compatible with: DH600

5.8" Optical Cover Diameter: 147 mm (5.8 inches) Compatible with: DH801*





Power Adapter

D77H07-A1030

Input: 100~115VAC / Output: 24VAC 72VA

D77H07-A2030

Input: 220~230VAC / Output: 24VAC 72VA



Sunshield

Height: 89.9 mm (3.5 inches) Diameter: mm (7.5 inches) Compatible with: DH600

Height: 129.5 mm (5.0 inches) Diameter: 190 mm (7.5 inches) Compatible with: DH801*





The D77H07 is an power supply, with integrated connection for communication and alarm, designed for outdoor applications with the DynaHawk™ speed dome camera, providing water resistent protection. The unit has one fused output and can handle a total load of

Dimension: 186.5×147 mm (7.3×5.8 inches) Weight: 2.6 kg (5.8 lbs) D77H07-P1030 (Input: 110~115VAC / Output: 24VAC 72VA) D77H07-P2030 (Input: 220~230VAC / Output: 24VAC 72VA)



16 17

Indoor Mounting Accessories

There are three types of Indoor dome camera mounting methods: hard-ceiling mounting, in-ceiling mounting, and pendent mounting. With the Indoor Mounting Kit, the DynaHawk™ 701 series will be able to apply to all other dome camera mounting accessories, such as straight tube, wall mount, corner mount and pole mount.




Hard Ceiling Mount: DH701

DH77H06-HC

Height: 21 .4 mm (0.8 inches)

Diameter of the three holes: 4.5 mm (0.2 inches) Diameter of the bracket: 158 mm (6.2 inches)

Weight: 0.2 kg (0.4 lbs)



T-Bar Ceiling Mount: DH701

D77H06-TB

Height: 160 mm (6.3 inches) Diameter: 180 mm (7.1 inches) Weight: 0.5 kg (1.1 lbs)









Indoor Mount Kit: DH701

D77H05-IMK

For mounting indoor dome camera onto a gooseneck/straight tube. Height: 74 mm (2.9 inches) Diameter: 140 mm (5.5 inches)

Weight: 0.5 kg (1.1 lbs)



Hard Ceiling Mount: DH500

DH500HC

Height: 19 mm (0.75 inches) Diameter of the three holes: 4.5 mm (0.2 inches) Diameter of the bracket: 58 mm (6.2 inches) Weight: 0.2 kg (0.4 lbs)






T-Bar Ceiling Mount: DH500

DH500TB1

Height: 85 mm (3.4 inches) Diameter: 180 mm (7.1 inches) Weight: 0.5 kg (1.1 lbs)






Indoor Mount Kit: DH500

D77H05-IMK5

For mounting indoor dome camera onto a gooseneck/straight tube. Height: 74 mm (2.9 inches) Diameter: 140 mm (5.5 inches) Weight: 0.5 kg (1.1 lbs)






Indoor/Outdoor Mounting Accessories

Straight Tube

D77H03-ST1/ST2


Height: 250/500 mm (9.8/19.7 inches) Diameter: 50 mm (2 inches) Weight: 1 kg/1.8kg (2.2 lbs/4 lbs) Compatible with: DH701/DH801*/DH500/DH600



Gooseneck Tube

D77H03-GT


Dimension: 298x385 mm (11.7x15.2 inches) Diameter: 92×42 mm (3.7×1.7 inches) Weight: 2.1 kg (4.6 lbs) Compatible with: DH701/DH801*/DH500/DH600



Mini Pendent Mount

D77H03-MP

Dimension: 184x104x115 2 mm (7 2x4 1x4 5 inches) Diameter: 44.5 mm (1.8 inches) Weight: 0.6 kg (1.3 lbs) Compatible with: DH701/DH801*/DH500/DH600



Wall Box Mounting

D77H05-WBM


Dimension: 270×166×95 (10.6×6.5×3.7 inches) Weight: 2.2 kg (4.8 lbs) Compatible with: D77H03-GT/D77H03-MP



Corner Standard Mounting Plate D77H05-CST

Dimension: 222x204x117 mm (8.7x8x4.6 inches) Weight: 2 kg (4.4 lbs)


Compatible with: D77H03-GT/D77H03-MP



Corner Plate Mini

D77H05-CSTM

Dimension: 270x166x95 (10.6x6.5x3.7 inches) Weight: 0.8 kg (1.8 lbs) Compatible with: D77H03-MP




Corner Wide Box Mounting

D77H05-CWB

Dimension: 232×234×205 mm (9.1×9.2×8.1 inches) Weight: 2.7 kg (6 lbs)

Compatible with: D77H03-GT/D77H03-MP



Corner Thin Box Mounting

D77H05-CTB


Dimension: 300x164x254 mm (11.8x6.5x10 inches)
Weight: 3 kg (6.7 lbs) Compatible with: D77H03-GT/D77H03-MP



Pole Wide Direct Mounting

D77H05-PWD

Dimension: 270×170×60 mm (10.6×6.7×2.4 inches) Recommend Pole Diameter: 112~130 mm (4.4~5 inches) Compatible with: D77H03-GT/D77H03-MP



Pole Thin Direct Mounting

D77H05-PTD

Dimension: 232x136x50xmm (9.1x5.4x2 inches) Recommend Pole Diameter: 112~140 mm (4.4~5.5 inches) Weight: 0.7 kg (1.6 lbs)


Compatible with: D77H03-GT/D77H03-MP



Pole Wide Box Mounting

D77H05-PWB

270×166×155 mm (10.6×6.5×6.1 inches) Recommend Pole Diameter: 112~140 mm (4.4~5.5 inches) Compatible with: D77H03-GT/D77H03-MP



Pole Thin Box Mounting

D77H05-PTB

Dimension: 291x136x242 mm (11.5x5.4x9.5 inches) Recommend Pole Diameter: 112–130 mm (4.4–5 inches) Weight: 3.1 kg (6.9 lbs) Compatible with: D77H03-GT/D77H03-MP



MKPB-DOME-PC-0704-EN01-LS

19

18