

LCD	Item series	HS-IP1910 Plus series
	Display	New 4 inch IPS touch screen, 960*640resolution
Video Mode	CVBS *	1 channel BNC input, NTSC/PAL (Auto adapt)*(Optional) PTZ control, RS485 control, Baud 600-115200bps, compatible with more than 30 protocols such as PELCO-D/P, Samsung, Panasonic etc
	IP camera test 8K/H.265/H.264	IP Discovery/Quick ONVIF/IPC test /RTSP play /Client APK
	Rapid Video	Auto view the video, create testing report
	HIKVISION test tool	Support batch activate HIKVISION cameras and modify IP address, modify password etc. Self-defined modify channel name, can quickly change H.264 and H.265 video, open wide dynamic mode. Factory restore, etc. Support reset password and set video occlusion alarm of HIKVISION cameras.
	DAHUA test tool	Support batch activate DAHUA cameras and modify IP address,username and password. Self-defined modify channel name.
	HD Coaxial test*	8MP TVI camera test, 3840 x 2160P 12.5/15 FPS,UTC control/ call OSD menu*(Optional) 8MP CVI camera test, 3840 x 2160P 12.5/15 FPS, UTC control / call OSD menu*(Optional) 8MP AHD test, 3840 x 2160P 15FPS, UTC control / call OSD menu*(Optional) Auto HD app, auto recognize HD coax camera type and resolution, support snapshot, video record& playback, coaxial PTZ & call OSD menu*(Optional)
	Zoom Image	4x zoom, to enlarge image, Screen snapshot, record, save, view and record and play back
	12V/3A power	Output DC12V/3A power out, supply temporarily power for the camera
	PoE power output	48V PoE power output, max power 25.5W
Cable test	Digital Cable tracer *	Search BNC cable, network cable and telephone cable from the mess cables. Cable search and UTP cable can test at the same time *(Optional)
	UTP cable test	Test UTP cable connection status and display on the screen. Can detect the near-end, mid-end and far-end fault point of the RJ45 cable plug.
Tester Play	Screen projection:	Tester, mobile phone and PC display at the same time (For android version mobile phone)
Network test	Trace route, Link monitor,DHCP server, port flashing, Ping test	
Wi-Fi	Built in WIFI, speeds 150M, display wireless camera image	
Audio test	1 channel audio signal input, test whether sound normal.	
Power management	Display DC 12V input & output voltage and power in real time	
Data monitor	Captures and analyzes the command data from controlling device, also can send hexadecimal	
External power supply	DC 12V 1A	
Battery	Built-in Lithium ionbattery 7.4 V / 2600mAh	
Rechargeable	After charging 3-4 hours, normal working time 9 hours	
Operation setting	OSD menu,select your desired language: English, Portuguese, Korean, Russian, Italian, French, Polish, Spanish, Japanese, Turkish, Deutsch, Serbian, Czech, Vietnamese etc	
Auto off	1-30 (mins)	
Working Temperature	-10°C---+50°C	
Working Humidity	30%-90%	
Dimension/Weight	160mm x 100mm x 45mm /0. 36kg	