

iDS-2CD6024FWD-A/F



Key Features

- Up to 2 megapixel (1920×1080) @ 30 fps resolution
- Standard video compression with high compression ratio.
- Progressive scan CMOS
- ROI function(Region of Interest)
- Built-in Micro SD / SDXC card slot, up to 64GB
- Support 3D DNR
- Wide dynamic range , up to 120dB
- Support face capture
- Support auto exposure on face area(exposure parameters can be adjusted automatically in different environment to see the clear face image)
- The accuracy rate of face capture is more than 90% according to the specified installation position
- Support face detection, face tracking for walkbys and face capture filtering to obtain the optimal face picture.
- Support over 15 face detection and capture at the same time.
- ABF(Auto Back Focus)
- IR cut filter with auto switch
- Built-in microphone, two-way audio
- Support DC/AC/PoE power modes
- Up to 20 channels live view at the same time
- Auto-iris, electronic shutter, BLC for different surveillance environments
- Support local analog video output for adjustment and installation
- LOGO picture can be overlaid on video
- Other functions: IP address filtering, anonymous access, PTZ control, alarm, reset button, mirror, etc.

● Application Scenarios

Suitable for station, subway, residential area, market, bank, hotel, passageway, etc.

Requirments of installation position

The maximum width of captured area is 2.5m. Installation postion can refer the following:

Width of captured carea W(m)	Monitoring distance U(m)	Focal length(mm)	Installation height (m)	A(degree)
2	5	12	2.6	13°±3°
2.5	6	12	2.8	13°±3°

Specification


Model	iDS-2CD6024FWD-A/F
Parameter	2 Megapixel CMOS ICR Intelligent Network Box Camera
Camera	
Image Sensor	1/2.8" Progressive Scan CMOS
Min. Illumination	Color: 0.01 Lux @ (F1.2, AGC ON) B/W: 0.001 Lux @ (F1.2, AGC ON)
Shutter Speed	1 s to 1/100,000 s
Slow Shutter	Support
Lens Mount	C/CS mount
Auto-iris	DC drive
Day & Night	IR cut filter with auto switch
Digital Noise Reduction	3D DNR
Wide Dynamic Range	120dB
ABF	Support
Compression Standard	
Video Compression	H.264/MPEG4/MJPEG
H.264 Type	Baseline Profile / Main Profile / High Profile
Video Bit Rate	32 Kbps – 16 Mbps
Audio Compression	G.711/G.722.1/G.726/MP2L2
Audio Bit Rate	64Kbps(G.711) / 16Kbps(G.722.1) / 16Kbps(G.726) / 32-128Kbps(MP2L2)
Image	
Max. Resolution	1920 × 1080
Frame Rate	50Hz: 25fps(1920 × 1080, 1280 × 960, 1280 × 720) 60Hz: 30fps(1920 × 1080, 1280 × 960, 1280 × 720)

BLC	Support, zone optional
HLC	Support
Image Setting	Saturation, Brightness, Contrast adjustable by client software or web browser
Day/Night Switch	Auto/Schedule/Triggered by Alarm In
ROI	Support
Picture Overlay	LOGO picture can be overlaid on video with 128x128 24bit bmp format
Network	
Network Storage	NAS(NFS, SMB/CIFS), edge recording
Protocols	TCP/IP,ARP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP, PPPoE,NTP,UPnP,SMTP,SNMP,IGMP,802.1X,QoS,IPv6,Bonjour
Security	User Authentication, Watermark, IP address filtering, Anonymous access
Standard	ONVIF, PSIA, CGI, ISAPI
Intelligent	
Behavior Analysis	Face capture
Alarm Trigger	Defocus Detection , Scene Change, Audio Abnormal ,Motion detection, Tampering alarm, Network disconnect, IP address conflict, Storage exception
Interface	
Audio Input	1-ch 3.5 mm audio interface, Mic in/Line in. 1 built-in Microphone
Audio Output	1-ch 3.5 mm audio interface
Communication Interface	1 RJ45 10M/100M Ethernet port, 1 RS-485 interface and 1 RS-232 interface
Alarm Input	1
Alarm Output	1
Video Output	1Vp-p composite output (75 Ω /FNC)
On-board storage	Built-in Micro SD/SDXC slot, up to 64 GB
Reset Button	Yes
General	
Operating Conditions	-30 °C – 60 °C (-22 °F – 140 °F) Humidity 95% or less (non-condensing)
Power Supply	24 V AC \pm 10%, 12 V DC \pm 10%, PoE (802.3af)
Power Consumption	Max. 6 W (Max. 9W with IR cut filter on)
Dimensions	69.8×58×145 mm (2.68" × 2.56" × 5.70")
Weight	830 g (1.83 lbs)

Order Models

iDS-2CD6024FWD/F, iDS-2CD6024FWD-A/F

Dimensions



Accessories



Indoor wall mount
DS-1212ZJ



Outdoor Wall Mount Bracket
DS-1213ZJ



Outdoor camera housing
DS-1322HZ-C/H/CW/HW



Indoor Camera Housing
DS-1320HZ

Lens



HV1140D-8MPIR
8MP vari-focal & auto-iris lens



HV3816D-8MPIR
8MP vari-focal & auto-iris lens