

LINEA 11 A IP CAMERA HOUSING

Patented

KIT11A – IP

*Weatherproof housing,
RJ45 Connector,
Heater with thermostat,
Blower kit, Wall
bracket, RAL9002*



IP HOUSING

Specifically designed to meet the high performances required by the ultimate generation of digital IP cameras.

FULL OPTIONAL

Wide range power supply, heater and blower kit can be supplied factory installed.

USER FRIENDLY

The Ethernet sealed RJ45 receptacle on the back cap (patent pending) assures a quick, safe and reliable on site connection.

SUITABLE FOR OUTDOOR AND INDOOR

Weatherproof rated, the integrated sunshield and the large window guarantee clear images and no vignetting



tekno system[®]
Italian design for CCTV since 1979

Tekno System S.p.A.
Via Rostoncello, 1 - 36010 Carrè – Italy
Phone: +39 0445 314324 | Fax: +39 0445 314319
Email: info@teknoystem.eu | Web: www.teknoystem.eu

rev. 040310

Page 1 / 4







TECHNOLOGY HIGHLIGHTS

- | | | |
|--|---------------------------|--------------------------------------|
| ✓ Ethernet sealed RJ45 receptacle | ✓ Extruded Aluminium Body | ✓ Designed for IP and analog cameras |
| ✓ Indoor / Outdoor Installations | ✓ ABS Front and Back Caps | ✓ Glass Window |
| ✓ Patented Slide and Hang Opening System | ✓ Integrated Sunshield | ✓ Patent Pending |
| | ✓ IP66 (EN60529) | |





MODELS

ORDER CODE	Wall bracket	Sunshield	IP Rate	Heater	Blower 12VDC	Wide range power supply
KIT11A/300IP	●	●	IP66			
KIT11A/300IP + HT	●	●	IP66	●		
KIT11A/300IP + HT + V11/230; V11/24	●	●	IP44	●	●	
KIT11A/300IP + HT + ALWR	●	●	IP66	●		●
KIT11A/300IP + HT + ALWR + V11/12	●	●	IP44	●	●	●

ACCESSORIES

HT/12-24	Heater with thermostat	
V11/12	Blower kit with thermostat	
ALWR	Wide range power supply	
FACRJ45	Field attachable connector RJ45	
EL	Camera height adjustment kit	
BW9H6	Wall mount bracket	

RELATED PRODUCTS

PA/1	Pole mount adapter for one bracket	
PA/2	Pole mount adapter for two brackets	
CM	Corner mount adapter	
R2B50	Bracket for illuminators	



SPECIFICATION

General

- Extruded aluminium body
- ABS UV resistant front and back caps
- Integrated Sunshield
- RAL9002 Polyester powder coating
- Supplied with: instruction manual, silicagel bag, 1/4" camera fixing screw, BW9H6 wall bracket and swivel head

Mechanical

- Internal usable area: 85 x 75mm (3.34 x 2.95in)
- Internal usable length: 252mm (9.92in)
- Usable Glass Windows 83,5 x 63,6mm (3.28 x 2.50in) Horizontal / Vertical max size
- 3mm-Thick glass
- removable M16x1,5 cable glands
- Zinc coated screws
- Ethernet sealed RJ45 receptacle

Electrical

- Heater Thermostat T_{on} 15°C (59°F) \pm 5°C T_{off} 22°C (71.6°F) \pm 4°C
- Heater PTC 100-240V~ 40W
- Heater PTC 12-24V~ 20W
- Blower Thermostat T_{on} 37°C (98.6°F) \pm 4°C T_{off} 27°C(80.6°F) \pm 3°C
- Blower with double air filter, consumption 1W
- Camera power supply unit:
Vin 88-264V~ 47/63Hz
Vout 12VDC 2,1A

Environment

- Indoor / Outdoor applications
- Temperature range with heater: -20°C (-4°F) up to +50°C (+122°F)
- IP66 weatherproof rating (according to EN60529)
- CE according to EN61000-6-3, EN60950, EN50130-4
- RoHS compliant



Waterproof male connector
FACRJ45



Slide & hang system



Ceiling Mounting KIT 11 AC IP



