

# PSB series power supply



Enclosed, switch mode buffer power supply 13,8V DC, without automatic operation control

CODE: **PSB-501235** v1.0/VIII

EN

TYPE: **PSB 13.8V/3,5A enclosed switch mode buffer power supply**

## Features of the power supply:

- DC 13,8V/3,5A uninterruptible power supply\*
- wide AC input voltage range 176÷264V
- high efficiency 76%
- controlling of battery charging and maintaining
- protecting of battery against excessive discharging (UVP)
- battery charging current 0,5A
- additional accessories: automation module MPSB12 (technical outputs):
  - EPS technical output indicating AC power loss
  - PSU technical output indicating PSU failure
  - LoB technical output indicating battery low voltage
- battery output is full protected against short-circuit and reverse connection
- LED optical signalisation
- protections:
  - short-circuit protection SCP
  - over voltage protection OVP
  - surge protection
  - overload protection OLP
- warranty – 2 year from the production date



## DESCRIPTION

Buffer-type power supply units are intended for continuous power supply to devices that require stabilised voltage of **12V DC (+/-15%)**. The power supply provides a voltage of **U=13,8V DC** with an output current of **I=3A+ 0,5A battery charging\***. In case of power voltage decay, prompt switching to battery supply occurs. The power supply unit is protected against a short circuit, an overload, a surge or over voltage protection.

## TECHNICAL DATA

Supply voltage	176 ÷ 264V AC
Current consumption	0,6A@230VAC max.
Supply power	50W max.
Efficiency	76%
Output voltage	11V± 13,8VDC – buffer operation 9,5V±13,8V DC – battery operation
<b>Output current t<sub>AMB</sub>&lt;30°C</b>	<b>3A + 0,5A battery charging - see chart 1</b>
<b>Output current t<sub>AMB</sub>=40°C</b>	<b>2,1A + 0,5A battery charging - see chart 1</b>
Voltage adjustment range	12÷14V DC
Ripple voltage	120mV p-p max.
Battery charging current	0,5A max.
Short-circuit protection SCP	electronic, automatic recovery
Overload protection OLP	105-150% of power supply, automatic recovery
Overload protection (battery) OLP	polymer fuse (PTC)
Surge protection	varistors
Overvoltage protection OVP	>16V (automatic recovery)
Excessive discharge protection UVP	U<9,5 V (± 5%) – disconnection of battery
Optical signalisation	green LED- presence of AC voltage
Output of optical signalization	LED AC- presence of AC voltage LED DC- presence of DC voltage on power supply output
Additional accessories	Module MPSB12 (technical outputs)
Operation conditions	2-nd enviromental class, temperature: -10 °C+40 °C relative humidity 20%...90%, without condensation
Dimensions (LxWxH)	159 x 97 x 42 [mm]
Net/gross weight	0,48kg / 0,53kg
Protection class EN 60950-1:2007	I (first) - requires a protective conductor (PE)
Declarations, warranty	CE, RoHS, 2 year from the production date
Connectors	power-supply: Φ0,63±2,5 I/O PCB : Φ0,41±1,63 battery output BAT: 6,3F-2,5/40cm, output of optical signalization: plug 3-pin 5 mm

\* See chart 1

# PSB series power supply



Enclosed, switch mode buffer power supply 13,8V DC, without automatic operation control

## Output current vs temperature




Chart 1.  
Allowable output current from the power supply depending on ambient temperature.

## Dimensions and fitting of the PSB-501235 power supply

