

VIDEO DOOR ENTRY SYSTEMS & KITS ULTRA

1/3



UT9240M

METAL ULTRA INFORMATION MODULE









Metal version of info module for Ultra entrance panels, compatible with all systems. Automatic nameplate backlight switch-off during daytime hours via the twilight sensor for the paired audio or audio/video module. White nameplate lighting. Made with aluminium trim to increase resistance to impact and polymethyl methacrylate treated to increase resistance to UV rays while preventing yellowing and dulling. Dimensions: 1 Ultra module. Dimensions: $100 \times 90 \times 35 \, \text{mm}$

AWARDS

D E S I G N M I L A N O



VIDEO DOOR ENTRY SYSTEMS & KITS ULTRA

2/3



UT9240M

U1924UM	
METAL ULTRA INFORMATION MODULE GENERAL DATA	
Height (mm)	90
Width (mm)	100
Depth (mm)	35
Product color	Transparent, Aluminum
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory
COMPATIBLE SYSTEMS	
Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes
ELECTRICAL CHARACTERISTICS	
Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Maximum absorption (W)	0.4
HARDWARE FEATURES	
Backlight colour	White, Off
ENVIRONMENTAL AND COMPLIANCE FEATURES	
Protection rating (IP code)	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95



VIDEO DOOR ENTRY SYSTEMS & KITS

ULTRA

3/3



UT9240M

METAL ULTRA INFORMATION MODULE	
ENVIRONMENTAL AND COMPLIANCE FEATURES	
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007, EN 61000-6-3:2007+A1:2011)
FEATURES	
Product weight (g)	245
Type of finishing materials	Polycarbonate, Aluminium alloy