

**UT9260M****DIGITAL DIRECTORY MODULE WITH DISPLAY, ULTRA**

Digital directory module for Ultra entrance panel, compatible with all systems. Bluetooth connection for managing names in the directory using the installer's MyComelit app. Buttons for user selection and calling. Option of customising one button for direct calls to the switchboard, commercial activities, activation of an automated opening or a light. Equipped with a 3.5" colour graphic display. Can be paired with the numeric keypad module to directly call the user when the relevant code is known, or for the access control function with activation of the audio or audio/video module outputs and the system actuators. Dimensions: 100x90x35 mm.

**AWARDS**DESIGN  
MILANO



**UT9260M**

**DIGITAL DIRECTORY MODULE WITH DISPLAY, ULTRA**

**GENERAL DATA**

Type	Modular
Height (mm)	90
Width (mm)	100
Depth (mm)	35
Product weight (g)	400
Type of finishing materials	Polycarbonate
Product color	Black RAL9005, Transparent
Flush-mounted	Yes, with a dedicated accessory
Wall-mounted	Yes, with a dedicated accessory

**COMPATIBLE SYSTEMS**

Audio/video Simplebus 2 with power supply art. 4888C	Yes
Audio/video Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 2 with power supply art. 1210/1210A	Yes
Audio Simplebus 1	Yes
ViP	Yes

**DISPLAY**

Display type	Graphic LCD
Display size (")	3.5
Resolution (pixel)	320x240

**ELECTRICAL CHARACTERISTICS**

Type of power supply	Power supply from video door entry bus
Supply voltage	33VDC
Absorption in stand-by (W)	1.3
Maximum absorption (W)	2



**UT9260M**

**DIGITAL DIRECTORY MODULE WITH DISPLAY, ULTRA**

**HARDWARE FEATURES**

Call type	Digital
Type of buttons	Mechanical
Number of push-buttons (n°)	4
Backlight colour	Black
Clamps	D+ D- GND

**SETTINGS**

Backlighting display	Yes
Backlight brightness	Yes

**NETWORK AND COMMUNICATION PROTOCOLS**

Bluetooth	Yes
-----------	-----

**PROGRAMMING MODE**

ViP Manager software	Yes
----------------------	-----

**ENVIRONMENTAL AND COMPLIANCE FEATURES**

IP protection rating	IP65
Vandal Resistant rating (IK code)	IK08
Operating temperature (°C)	-25 ÷ 55
Operating humidity (RH max) (%)	25 ÷ 95
Environmental class	IV
CE certifications	RoHS II - 2011/65/UE (EN IEC 63000:2018), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

**MAIN FUNCTIONS**

No. of storable users (n°)	1500
Visual indications of system status	Yes
Customizable welcome message	Yes
	Yes