



A LIFETIME OF SECURITY

VUpoint professional video solution Product Catalogue

Now with
4MP
Professional
Cameras!



The new VUpoint is a professional video system, which includes high resolution cameras at resolutions of up to 4MP as well as an advanced cloud based video management system. Powered by RISCO Cloud, this integrated video solution provides unrivalled alarm verification capabilities. Installing video & alarm? RISCO's integrated solution is your best choice.



Professional P2P Video Solution

A variety of NVRs & IP Cameras to tailor a high resolution solution for every application.



One App. Integrated Solution

Integrated with RISCO's professional security systems for real time alarm verification, Live View and recording.



Professional Windows VMS






Cloud-based PC application providing multi-site video live view and playback.

	Full HD 2MP WiFi Camera Line				
	WiFi Cube Camera	WiFi Eyeball Camera	WiFi Bullet Camera	WiFi PT Camera	4MP Cube Camera
					
Image Sensor	1/2.7" 2 Megapixel CMOS	1/2.7" 2 Megapixel CMOS	1/2.7" 2 Megapixel CMOS	1/2.7" 2 Megapixel CMOS	1/3" 4 Megapixel CMOS
Lens	2.8 mm	2.8 mm	2.8 mm	3.6 mm	2.8 mm/F2.0
FDV-H	105°	114.6°	114.6°	89°	97°
Day/Night	ICR	ICR	ICR	ICR	ICR
WDR	DWDR				DWDR
Max IR Distance	10m	20m	30m	10m	10m
Video Compression	H.265	H.265	H.265	H.265	H.265
Max Resolution	1080P(1920×1080)	1080P(1920×1080)	1080P(1920×1080)	1080P(1920×1080)	4M (2560 × 1440)
Frame Rate	30fps@1080P	30fps@1080P	30fps@1080P	30fps@1080P	30fps@4MP
Multi-Streaming	2 streams	2 streams	2 streams	2 streams	2 streams
Pan/Tilt/Zoom				Pan / Tilt / Digital Zoom	
Compatibility	ONVIF, CGI	ONVIF,CGI	ONVIF,CGI	ONVIF, CGI	ONVIF, CGI
Audio In/Out	Built In Speaker & Mic		Built in Mic	Built In Speaker & Mic	Built In Speaker & Mic
Memory Slot	Micro SD, Max. 256GB	Micro SD, Max. 128GB	Micro SD, Max. 128GB	Micro SD, Max. 128GB	Micro SD, Max. 256GB
Ingress Protection		IP67	IP67		
Working Temperature	-10°C ~ +45°C	-20°C~+60°C	-20°C~+60°C	-10°C ~ +45°C	-10°C ~ +45°C
Power	DC12V Max. 2.9W	DC12V Max. 4.7W	DC12V Max. 4.8W	DC12V Max. 7.5W	DC12V/PoE Max. 3.3W
Model	RVCM11W1500	RVCM32W1600	RVCM52W1400	RVCM61H1700	RVCM11P1800

4MP Professional Camera Line

4MP Dome Camera	4MP Bullet Camera	4MP Eyeball Camera	4MP VF Bullet Camera	4MP VF Eyeball Camera	4MP X25 PTZ Camera
					
1/3" 4 Megapixel CMOS	1/3" 4 Megapixel CMOS	1/3" 4 Megapixel CMOS	1/3" 4 Megapixel CMOS	1/3" 4 Megapixel CMOS	1/2.8" STARVISTM CMOS
2.8 mm/F2.0	2.8 mm/F2.0	2.8 mm/F1.6	2.8 mm-12 mm/F1.7	2.8 mm-12 mm/F1.7	4.8 mm-120 m/F1.6-F4.0
93°	93°	102°	98°-31°	98°-31°	60°-2.5°
ICR	ICR	ICR	ICR	ICR	ICR
WDR	WDR	WDR	WDR	WDR	WDR
30m	30m	30m	50m	50m	100m
H.265	H.265	H.265	H.265	H.265	H.265
4M (2560 × 1440)	4M (2560 × 1440)	4M (2560 × 1440)	4M (2560 × 1440)	4M (2560 × 1440)	4M (2560 × 1440)
30fps@4MP	30fps@4MP	30fps@4MP	30fps@4MP	30fps@4MP	30fps@4MP
2 streams	2 streams	2 streams	2 streams	2 streams	3 streams
					PTZ
ONVIF, CGI	ONVIF, CGI	ONVIF, CGI	ONVIF, CGI	ONVIF, CGI	ONVIF, CGI
		Built-in MIC			
		Micro SD, Max. 256GB	Micro SD, Max. 256GB	Micro SD, Max. 256GB	Micro SD, Max. 256GB
IP67	IP67	IP67	IP67	IP67	IP66
-40°C to +55°C	-40°C to +55°C	-40°C to +60°C	-30°C to +60°C	-30°C to +60°C	-40°C to +70°C
DC12V/PoE Max. 4.9W	DC12V/PoE Max. 5.0W	DC12V/PoE Max. 6.6W	DC12V/PoE Max. 7.4W	DC12V/PoE Max. 7.4W	DC12V/PoE+ Max. 21W
RVCM32P1900	RVCM52P2000	RVCM72P2100	RVCM52P2200	RVCM72P2300	RVCM82E2500

VUpoint NVR

	4ch NVR	4ch PoE NVR	8ch PoE NVR	16ch NVR	32ch NVR
					
Model	RVNVR040020	RVNVR04002P	RVNVR08002	RVNVR16002	RVNVR324K1F
System					
Audio and Video					
IP Camera Input	4 Channel	4 Channel	8 Channel	16 Channel	32 Channel
	Two-way Talk1 Channel Input, 1 Channel Output, RCA				
Display					
Interface	1 HDMI, 1 VGA				
Recording					
Compression	H.264/H.265				
Resolution	8Mp/ 6Mp/ 3MP/ 4MP/1080P/ MJPEG/ 720P etc.				
Record Rate	80Mbps				120 bps
Bit Rate	16Kbps ~ 20Mbps Per Channel				
Record Mode	Continuous, Motion				
Network					
Interface	1 RJ-45 Port (10/100Mbps)				
PoE		4	8		
Storage					
Internal HDD	1 SATA III Port, Up to 10 TB capacity				
Electrical					
Power Supply	12V, 2A	48V, 1.5 A	48V/53V, 2A/1.8A	12V, 2A	12V, 4A
Power Consumption	NVR: <10W (Without HDD)	NVR: <10W (Without HDD) PoE: Max 25.5w for single port, 36w in total	NVR: <8.3W (Without HDD) PoE: Max 25.5w for single port, 72w in total	NVR: <10W (Without HDD)	NVR: 5.6Wc (Without HDD)
Environmental					
Operating Conditions	-10 °C to +55 °C (+10 °F to +131 °F), 10%~93%				
Storage Construction	0 °C to +40 °C (32 °F to 104 °F), 30%~85%				
Dimensions:	Smart 1U, 204.6mm × 206.4mm × 48.1mm (8.06" × 8.12" × 1.90") (W × L × H)	Smart 1U, 204.6mm × 206.4mm × 45.6mm (8.06" × 8.12" × 1.90") (W × L × H)	Smart 1U, 270mm × 206.5mm × 47.5mm (10.63" × 8.13" × 1.87") (W × L × H)	Smart 1U, 204.6mm × 206.4mm × 48.1mm (8.06" × 8.12" × 1.90") (W × L × H)	375.0mm × 282.9mm × 53.0mm (14.76" × 11.14" × 2.09") (W × L × H)
Net Weight:	0.45kg (0.99 lb) (without HDD)	0.45kg (0.99 lb) (without HDD)	0.70kg (1.43 lb) (without HDD)	0.45kg (0.99 lb) (without HDD)	1.5 kg (3.31 lb) (without HDD)
Certifications					
CE	EN62368-1; EN55032,EN55024, EN55035, EN61000-3-2, EN61000-3-3 EN50130-4				
FCC	Part 15 Subpart B				
RCM	EN55032, IEC 62368-1				

Accessories

RVCM32P1900	RVIM0A137 Junction box	RVIM1203W Wall mount	RVIM3152E Pole mount
			
RVCM52P2000	RVIM0A134 Junction box	RVIM3152E Pole mount	
			
RVCM72P2100	RVIM0A130 Junction box	RVIM1203W Wall mount	RVIM3152E Pole mount
			
RVCM52P2200	RVIM0A130 Junction box	RVIM3152E Pole mount	
			
RVCM72P2300	RVIM0A130 Junction box	RVIM1203W Wall mount	RVIM3152E Pole mount
			
RVCM82E2500	Included Wall mount	RVIM0A12 Water Proof Junction box	RVIM3A15 Pole mount
			
	RVIM4A151 Corner mount	RVIM2300C Ceiling mount	RVIM5A111 mount Adapter
			